


EM Recessed

EM-00004

Ø55mm/ Ø80mm/ Ø140mmx 32mm




LIGHT FORMS

Emergency

Specification



Recessed



Features

Available in black and white.

2 x Optics available

Wide Round - 150°

Corridor - 160°x60°

240lm

CCT - 5000K

CRI - >70

LiFePO4 6.4V 1500mAh
battery.

Discharge duration of >3 hours.

Class II

Made from polycarbonate.

0°C to 45°C operating
temperatures.

Photometry and additional documentation at:
[LightForms.com/products/emergency/EM Recessed/](https://LightForms.com/products/emergency/EM-Recessed/)

LightForms.com

Page 1

Europe@

LightForms.com

Asia@

LightForms.com

Manchester@

LightForms.com

EM Recessed

LIGHT FORMS

EM-00004

EM - 00004 - - - 03 - 750 - - - - -

1. Finish Options

White - WH
Black - BK

2. Nominal Power Options

250lm 6W - 03

3. Chip Options

70CRI 5000K - 750

4. Beam Degree Options

Wide (150°) - WI
Corridor (160°x60°) - CO

5. Testing Options

Auto Test - AUT
DALI - DAL


6. Accessories

80mm trim - T80
140mm trim - T140

Electrical Specification

Input Power (MAX)	3W
Frequency	50/60Hz
Input Voltage	200-240V
Discharge Efficiency	≥70%
Output Power	1.8W ± 0.3W
Power Factor	≥0.3%
Rated Input Current	≥0.03A
Full Load Output Voltage	DC 2.8-3.2V
Output Current Range	580mA ±10%
Surge	0.5KV
Withstand voltage	AC3750V
Short Circuit Protection	Pass
Over voltage protection	Pass

Dimensions




EM Recessed


LIGHT FORMS

EM-00004

Distribution



150°



160° x 60°

Warranty

5-year fixture warranty.
3-year battery warranty.

Operating temperature

Ta Max 45°C

Manufacturing & certification

Products are manufactured in and comply with the health, safety and environmental protection standards of the respective region in which they are sold.



Europe



United Kingdom



Greater India
and Middle East