


# Serpentine 60

SPT60 — LED  
62 mm x 80 mm



**LIGHT FORMS**

Curves

With its elegant curves, Serpentine adds a sophisticated touch to any interior. Available as individual luminaires, continuous runs, custom configurations, and in a wide range of colours and finishes.



## Features

Individual Fixture,  
Continuous Run or  
Custom Configuration

Direct/Indirect,  
Direct or Indirect  
Distribution

Up to 6044 lm/M and  
117 lm/W

Four Standard Output  
Options

Tunable White and  
RGB+W Options

Integral DALI, DMX,  
10V or Phase Driver

Dimming Down to 0%

Integral Downlight  
Spot Options

Integral Sensor  
Options

White, Black, Bronze  
or Custom RAL Finish

Custom shapes  
available, contact  
factory

Photometry and additional documentation at:  
[LightForms.com/products/all/serpentine60/](https://LightForms.com/products/all/serpentine60/)

# Serpentine 60

LIGHT FORMS

## Product Options

### Mounting Options

Vertical Suspended  
Rod Suspended  
Surface Mount  
Recessed

### Shape Options

Curve  
Soft Square  
Soft Triangle  
Obround  
Ellipse  
Custom

### CRI Options

80CRI  
90CRI

### CCT Options

2700K  
3000K  
3500K  
4000K  
6500K  
2700-6500K

### Control Options

Non Dimmable  
DALI  
1-10V  
DMX  
Wireless

### Direct Output Options @ 80CRI 4000K

Minimum (10W)	-	964 lm/m
Low (14W)	-	1435lm/m
Medium (25W)	-	2551lm/m
High (48W)	-	4341m/m
Tuneable Low		1252lm/m
Tuneable Medium		2279lm/m
RGBW		809m/m

### In-Direct Output Options @ 80CRI 4000K

Minimum(10W)	-	1203m/m
Low(14W)	-	1790lm/m
Medium(25W)	-	3183lm/m
High(48W)	-	5416lm/m
Tunable Low		1561lm/m
Tunable Medium		2843lm/m
RGBW		1009lm/m

### Lens Options

Clear Prismatic  
Opal Prismatic  
Opal

### Additions

DALI motion sensor  
Standard motion Sensor  
BASIC 3 hour emergency  
DALI 3 hour emergency

Click here to navigate to the online Product Configurator.



LightForms.com

Page 2

Europe@

LightForms.com

Asia@

LightForms.com

Manchester@

LightForms.com


# Serpentine 60

LIGHT FORMS

SPT60


## Dimensions

---



## Distribution


---



# Serpentine 60

## LIGHT FORMS

### Body Colours

	9005	Jet Black		7022	Umbrage Grey
	9010	Pure White		7023	Concrete Grey
	1001	Beige		7024	Graphite Grey
	1002	Sand Yellow		7026	Granite Grey
	1007	Daffodil yellow		7030	Stone Grey
	1034	Pastel Yellow		7032	Pebble Grey
	1035	Pearl Beige		7035	Light Grey
	2004	Pure Orange		7037	Dusty Grey
	3011	Brown Red		7043	Traffic Grey B
	3012	Beige Red		7047	Telegrey 4
	4002	Red Violet		7048	Pearl Mouse Grey
	5001	Green Blue		8004	Copper Brown
	5002	Ultramarine Blue		8015	Chestnut Brown
	5008	Grey Blue		8019	Grey Brown
	5009	Azure Blue		8025	Pale Brown
	5011	Steel Blue		9001	Cream
	5012	Light Blue		9002	Grey White
	5013	Cobalt Blue		9003	Signal White
	5025	Pearl Gentian Blue		9004	Signal Black
	6000	Patina Green		9006	White Aluminium
	7009	green Grey		9007	Grey Aluminium
	7010	Tarpaulin Grey		9011	Graphite Black
	7012	Basalt Grey		9016	Traffic White
	7016	Anthracite Grey		9017	Traffic Black
	7021	Black Grey			

Light Forms also covers an extensive range of premium finishes, including specialist metallic finishes.




YW387I  
Ordos Sable




M3000I  
Nickel Metallic



S2304I  
Metallic Fine Texture




YX355F  
Mars Sable



YW255F  
Golden Beach



Y2205I  
Golden Splendour




Y2M30I  
Dark Bronze



RW404I  
Copper Coarse



EW002E  
Aluminium Metallic  
Gloss



Y2214F  
Anodic Bronze



For full details  
and links to the  
Interpon powder  
range, click here.

# Serpentine 60


## LIGHT FORMS

### Housing


100% recyclable, extruded architectural grade aluminium with minimum 2mm thickness.

### Suspension mount canopy options


Number of suspension points may vary depending on size.



CS - Central Suspended



VS - Vertical Suspended



RD -Rod Suspended

\*Length to be confirmed by site, not adjustable on site

### Integral Downlights

Optional, aimable accent downlight spots deliver up to 1430 lumens with beam spreads from 15° to 40°.

Limitations apply. See Downlight Spots chart for further information.

### Integral sensors

Optional, presence (PRES), DALI-compatible PIR presence (DALI/PRES) and daylight harvesting (PHOTO) sensors available. Contact Light Forms for further information.

### Weight

Approximately 2380 grams per linear metre. Weight will increase with the addition of integral downlights, sensors, and emergency batteries and may vary further depending on mounting and other options.

### Operating temperature

Luminaire MUST be installed and operated ONLY in dry or damp environments where the ambient temperature ranges from -20°C to 50°C. Luminaire operation in environments outside this temperature range voids the warranty AND may damage the product or adversely impact lamp life, lumen output and colour consistency.

### Warranty

5-year limited warranty.

### Manufacturing & certification

Products are manufactured in and comply with the health, safety and environmental protection standards of the respective region in which they are sold.



Europe



United Kingdom



Greater India  
and Middle East

# Serpentine 60

LIGHT FORMS

SPT60

Examples of Serpentine 60 in use

---



Details of installation