


Vela 100

Family Photometry Data



LIGHT FORMS


Down/Spotlights

Output	Current (mA)	Power (W)	Board	Beam Angle (FWHM)	Lumens	Lumens/Watt
MIN	350mA	131	2700K >90CRI	20	1391	1063
				31	1478	113
				42	1459	1115
				50	1415	1081
MED	400mA	151		20	1553	103
				31	1650	1094
				42	1628	108
				50	1733	1047
HIGH	450mA	171		20	1704	995
				31	1810	1058
				42	1786	1044
				50	1733	1012
MAX	500mA	192		20	1854	96.7
				31	1970	1027
				42	1994	1014
				50	1886	98.3
MIN	350mA	131	3000K >90CRI	20	1454	111.1
				31	1545	118.1
				42	1525	116.5
				50	1479	113
MED	400mA	151		20	1606	106.5
				31	1706	113.1
				42	1684	111.6
				50	1633	108.3
HIGH	450mA	171		20	1773	103.6
				31	1884	110.1
				42	1859	108.6
				50	1803	105.3
MAX	500mA	192		20	1950	101.7
				31	2072	108
				42	2044	106.6
				50	1983	103.4
MIN	350mA	131	3500K >90CRI	20	1573	120.3
				31	1672	127.8
				42	1650	126.1
				50	1600	122.3
MED	400mA	151		20	1743	115.3
				31	1852	122.8
				42	1827	121.2
				50	1772	117.5
HIGH	450mA	171		20	1912	111.7
				31	2032	118.7
				42	2005	117.1
				50	1944	113.6
MAX	500mA	192		20	2081	108.5
				31	2211	115.3
				42	2182	113.8
				50	2116	110.3

*Driver power factor 0.92

Vela 100

Family Photometry Data



LIGHT FORMS

Down/Spotlights

Output	Current (mA)	Power (W)	Board	Beam Angle (FWHM)	Lumens	Lumens/Watt
MIN	350mA	13.1	4000K >90CRI	20	1583	121
				31	1682	1285
				42	1660	1268
				50	1610	123
MED	400mA	15.1		20	1799	1193
				31	1912	126.7
				42	1886	125.1
				50	1830	121.3
HIGH	450mA	17.1		20	1974	115.3
				31	2097	122.5
				42	2069	120.9
				50	2007	117.3
MAX	500mA	19.2		20	2148	112
				31	2283	119
				42	2252	117.4
				50	2185	113.9
MIN	350mA	13.1	3000K >80CRI	20	1676	128.1
				31	1781	136.1
				42	1757	134.3
				50	1705	130.3
MED	400mA	15.1		20	1906	126.4
				31	2026	134.3
				42	199	132.5
				50	1939	128.5
HIGH	450mA	17.1		20	2082	121.6
				31	2212	129.2
				42	2183	127.5
				50	2117	123.7
MAX	500mA	19.2		20	2257	117.7
				31	2398	125
				42	2366	123.4
				50	2295	119.7
MIN	350mA	13.1	4000K >80CRI	20	1811	138.4
				31	1924	147.1
				42	1899	145.1
				50	1842	140.8
MED	400mA	15.1		20	2060	136.5
				31	2189	145.1
				42	2160	143.2
				50	2095	138.9
HIGH	450mA	17.1		20	2249	131.4
				31	2390	139.6
				42	2358	137.8
				50	2287	133.6
MAX	500mA	19.2		20	2438	127.1
				31	2591	135.1
				42	2557	133.3
				50	2480	129.3

*Driver power factor 0.92